## NSN 5935-01-125-2432

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-125-2432

Body Style:
Straight type
Overall Length:
5.717 inches
Overall Height:
0.669 inches
Overall Width:
0.473 inches
Environmental Protection:
Shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.110 inches
Distance Between Mounting Facility Centers:
5.400 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode and unable to decode
Included Contact Quantity:
96 single mating end single contact grouping
Included Contact Type:

**Special Features:** 

Round socket single mating end single contact grouping

Side mounting

## NSN 5935-01-125-2432

Electrical Receptacle Connector - Page 2 of 2



Precious N	Material And	Location:
------------	--------------	-----------

Contact surfaces gold

**Precious Material And Weight:** 

0.096 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0