NSN 5935-01-125-3699

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-125-3699

Body Style: Right angle type **Overall Length:** 2.490 inches **Overall Height:** 0.539 inches **Overall Width:** Between 0.335 inches and 0.360 inches **Unthreaded Mounting Hole Diameter:** 0.073 inches **Distance Between Mounting Facility Centers:** 2.350 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Material Specification:** Qq-b-750, comp a federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14f, ty sdgf military specification single material response single mating end **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 42 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

NSN 5935-01-125-3699

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location
Contact surfaces gold
Precious Material And Weight:
0.042 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14f spec.