NSN 5935-01-125-3702

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-125-3702 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.040 inches **Overall Height:** 0.679 inches **Overall Width:** 0.308 inches **Environmental Protection:** Vibration resistant and shock resistant and moisture resistant **Unthreaded Mounting Hole Diameter:** Between 0.091 inches and 0.101 inches **Distance Between Mounting Facility Centers:** Between 1.793 inches and 1.807 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 31 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end and jackscrew Shell Type: **Connector Locking Method:** Post jacksocket **Thread Length:** 0.199 inches **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 56

Thread Size:

0.086 inches

NSN 5935-01-125-3702

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum alloy 380.0 or aluminum alloy 6061
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification 1st material response or qq-a-591, t6 federal specification 2nd material response
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
31 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.031 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Mil-g-45204 spec.

Mil-std (military Standard):

No Fiig: A039b0