

View Online at <https://aerobasegroup.com/nsn/5935-01-125-6716>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.250 inches

Overall Height:

0.734 inches

Overall Width:

0.390 inches

Environmental Protection:

Corrosion resistant and thermal shock resistant and shock resistant and humidity resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

34 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

48

Thread Size:

0.099 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Glass fiber single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end

Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.034 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.