NSN 5935-01-125-6717

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-125-6717

Body Style: Right angle type **Overall Length:** 3.840 inches **Overall Height:** 0.580 inches **Overall Width:** 0.253 inches **Environmental Protection:** Shock resistant and vibration resistant and humidity resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.097 inches **Distance Between Mounting Facility Centers:** 3.640 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 2, cl 1, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 66 single mating end single contact grouping

Precious Material And Location: Contact surfaces gold

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-125-6717

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.066 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.