NSN 5935-01-125-8289

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-125-8289

| view Online at https://aerobasegroup.com/hsh/5955-01-125-6269 |
|--|
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.110 inches |
| Overall Diameter: |
| 0.630 inches |
| Cable Entrance Diameter: |
| 0.150 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Tnc single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Split |
| Connector Locking Method: |
| Internally threaded shell |
| Connector Cable Strain Relief Method: |
| Crimp type |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Beryllium single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-c-530 federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Silver |
| Shell Surface Treatment Specification: |
| Qq-s-365 federal specification single treatment response |
| Shell Material Specification: |

Included Contact Quantity:

1 single mating end single contact grouping

Qq-b-626 federal specification single material response

NSN 5935-01-125-8289

Electrical Plug Connector - Page 2 of 2



| Included | Contact | Ty | pe: |
|----------|---------|----|-----|
|----------|---------|----|-----|

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contacts gold and shell silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.