## NSN 5935-01-126-0141

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-126-0141 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** Between 2.112 inches and 2.122 inches **Overall Diameter:** Between 1.922 inches and 1.954 inches **Distance From Mounting Shoulder To Front Face:** Between 1.956 inches and 1.966 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.572 inches **Threaded Device Type:** Hub **Mating End Quantity: Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 **Connector Locking Method:** Bayonet pin **End Application:** B-52g/h oas Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping

Shell Material: Aluminum alloy

## NSN 5935-01-126-0141

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel and cadmium
Included Contact Quantity:
16 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contacts gold
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0