## NSN 5935-01-126-2427

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-126-2427

Body Style:
Straight shape
Overall Length:
2.680 inches
Overall Height:
1.680 inches
Overall Width:
0.300 inches
Body Length:
1.760 inches
Unthreaded Mounting Hole Diameter:
0.100 inches
Distance Between Mounting Facility Centers:
1.600 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Latch
Operating Tempurature Rating:
Between -55.0 degrees celsius and 105.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyester glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2
federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:

Wire wrap single mating end single contact grouping

**Included Contact Quantity:** 

20 single mating end single contact grouping

## NSN 5935-01-126-2427

Electrical Receptacle Connector - Page 2 of 2



## Included Contact Type: Square pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig:

Mil-std (military Standard): Mil-g-45204 spec.

A039b0