NSN 5935-01-126-3697

Telephone Jack - Page 1 of 2

Electrical Insulation Feature:

Insulated from panel



View Online at https://aerobasegroup.com/nsn/5935-01-126-3697

modiated from parior
Body Style:
Coaxial hole or slot mounted
Overall Length:
3.250 inches
Overall Height:
0.810 inches
Body Diameter:
0.530 inches
Mounting Hole Diameter:
0.156 inches
Mounting Bushing Length:
0.570 inches
Accommodated Finger Type:
Test prod single finger
Finger Accommodation Diameter:
0.053 inches single finger
Finger Accommodation Length:
0.190 inches single finger
Mounting Bushing Diameter:
0.447 inches
Jack Contact Arrangement Designator:
Jack Contact Arrangement Designator: J16
-
J16
J16 Mounting Facility Type And Quantity:
J16 Mounting Facility Type And Quantity: 1 unthreaded hole
J16 Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type:
J16 Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse
J16 Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type:
J16 Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material:
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator Material:
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator Material: Plastic polytetrafluoroethylene insulator
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator Material: Plastic polytetrafluoroethylene insulator Precious Material And Location:
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator Material: Plastic polytetrafluoroethylene insulator Precious Material And Location: Contact and terminal surface gold
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator Material: Plastic polytetrafluoroethylene insulator Precious Material And Location: Contact and terminal surface gold Precious Material And Weight:
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator Material: Plastic polytetrafluoroethylene insulator Precious Material And Location: Contact and terminal surface gold Precious Material And Weight: 0.005 gold grains, troy
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator Material: Plastic polytetrafluoroethylene insulator Precious Material And Location: Contact and terminal surface gold Precious Material And Weight: 0.005 gold grains, troy Precious Material:
Mounting Facility Type And Quantity: 1 unthreaded hole Storage Type: General purpose unheated warehouse Terminal Type: Solder well Material: Plastic, polytetrafluoroethylene insulator Material: Plastic polytetrafluoroethylene insulator Precious Material And Location: Contact and terminal surface gold Precious Material And Weight: 0.005 gold grains, troy Precious Material: Gold

NSN 5935-01-126-3697

Telephone Jack - Page 2 of 2



O	·	T	4	
SHILL	ace	Trea	tme	nt.

Nickel body and copper body

Fsc Application Data:

Connectors, electrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400