NSN 5935-01-126-3701

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-126-3701 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 0.766 inches **Overall Diameter:** 0.859 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** Oct-98 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.562 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:**

Nickel

NSN 5935-01-126-3701

Mil-c-26074 spec.

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074 military specification single treatment response
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.010 gold grains, troy and 0.010 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27473 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):