## NSN 5935-01-126-3708

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-126-3708

**Body Style:** 

Right angle type

**Overall Length:** 

2.800 inches

**Body Height:** 

0.375 inches

**Environmental Protection:** 

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.188 inches

**Distance Between Mounting Facility Centers:** 

2.400 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

1 row of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg military specification single material response single mating end

**Included Contact Quantity:** 

21 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.021 gold grains, troy

## NSN 5935-01-126-3708

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.