Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-126-3708

New Online at https://defobdsegfoup.com/nsi//3303-01-120-3/00
Body Style:
Right angle type
Overall Length:
2.800 inches
Body Height:
0.375 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Mounting Facility Centers:
2.400 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping   Contact Material Specification:
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping Insert Material Specification:
Mil-m-14, type sdg military specification single material response single mating end
Included Contact Quantity:
21 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.021 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.