## NSN 5935-01-127-1876

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-127-1876 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape w/cable clamp **Overall Diameter:** 1.500 inches **Body Angle In Deg:** 45.0 **Cable Entrance Diameter:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** A10 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 2nd contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 80.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Cable clamp

**Distance From Centerline To Connector End:** 2.344 inches Thready Qty Per Inch (tpi): **Thread Size:** 1.312 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings

## NSN 5935-01-127-1876

Electrical Plug Connector - Page 2 of 2



## **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic polyamide single mating end **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 5 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.030 gold grains, troy and 0.030 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Special acme Shelf Life: N/a **Unit Of Measure:**

**Demilitarization:** 

No Fiig: A039b0