

View Online at <https://aerobasegroup.com/nsn/5935-01-127-2104>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.290 inches

Overall Height:

1.812 inches

Overall Width:

1.812 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.147 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Distance From Mounting Shoulder To Front Face:

0.790 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

16.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.219 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.438 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

12 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.024 gold grains, troy and 0.024 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27656 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.