

View Online at <https://aerobasegroup.com/nsn/5935-01-127-2989>

Thread Class:

2a

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Maximum Current Rating In Amps:

40.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

30000.0 single mating end single contact grouping

Connector Locking Method:

Externally threaded shell

End Application:

Ec-135

Thread Size:

1.750 inches

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Copper single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-c-14550, class 4 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 1, class 1 military specification 2nd treatment response single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-613 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-345 federal specification single treatment response

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Precious Material And Location:

Contact gold and shell silver

Precious Material:

Gold and silver

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-14550 spec.