
## NSN 5935-01-127-6005

Tip Jack - Page 1 of 2

**Electrical Insulation Feature:** 





Insulated completely **Identification Code Color:** Red **Body Style:** Rivet mounted **Mounting Bushing Length:** Between 0.297 inches and 0.327 inches **Body Length:** 0.530 inches **Overall Diameter:** 0.235 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 1200.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Mounting Bushing Diameter:** 0.134 inches **Bushing Thru-hole Accommodation Diameter:** 0.135 inches **Current Rating In Amps:** 5.0 Mounting Facility Type And Quantity: 1 bushing **Terminal Type:** Pin Material: Plastic insulator Material: Plastic insulator **Precious Material And Location:** Contact and terminal surfaces gold **Precious Material:** Gold Surface Treatment: Gold terminal

# NSN 5935-01-127-6005

Tip Jack - Page 2 of 2



### Surface Treatment:

Gold terminal

#### **Test Data Document:**

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-39024/15 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A03400