NSN 5935-01-127-6651

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-127-6651 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 2.312 inches **Overall Height:** 2.031 inches **Overall Width:** 2.031 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.843 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-01-127-6651

Electrical Receptacle Connector - Page 2 of 2



| Thread Length: |
|--|
| 0.375 inches and 0.675 inches |
| Thready Qty Per Inch (tpi): |
| 18 and 18 |
| Thread Size: |
| 1.438 inches and 1.750 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Included Contact Quantity: |
| 43 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.043 gold grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Unef and uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Δ030h0 |