Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-127-6652

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Rectangular shape center screwlock
Overall Length: 2.780 inches
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.460 inches
Overall Height:
1.123 inches
Overall Width:
0.725 inches
Environmental Protection:
Thermal shock resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1 Occurrent De sitting American and Oteles
Contact Position Arrangement Style:
88 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Polarization boss
Shell Type:
Solid
Connector Locking Method:
Screw
Thready Qty Per Inch (tpi):
32 Thread Since
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping

NSN 5935-01-127-6652

Electrical Receptacle Connector - Page 2 of 2



Plastic dially	phthalate single mating end
-	
	face Treatment Specification: military specification 1st treatment response single mating end single contact groupir
•	
Terminal Ty	
	mating end single contact grouping
	erial Specification:
Shell Materia	leral specification single material response single mating end single contact grouping
Stainless ste	
	al Specification: leral specification single material response
-	ial Specification:
	e sdg-f military specification single material response single mating end
	ntact Quantity:
	ting end single contact grouping
Included Co	
	t single mating end single contact grouping
	Interial And Location:
Contact surfa	
	Iterial And Weight:
0.088 gold gr	-
Precious Ma	-
Gold	
	es Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	tion:
No	
Fiig:	
A039b0	
Mil-std (milit	ary Standard):
Mil-g-45204 :	Spec.