# NSN 5935-01-128-1467

Plastic diallyl phthalate single mating end

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-128-1467 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 3.350 inches **Overall Width:** 0.390 inches **Body Height:** 0.400 inches **Environmental Protection:** Vibration resistant and thermal shock resistant and corrosion resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Length:** 0.150 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** 

# NSN 5935-01-128-1467

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

60 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Jackscrew type-female and location-right handandjackscrew type-male and location-left hand

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.060 gold grains, troy

#### **Precious Material:**

Gold

# **Thread Series Designator:**

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

## Demilitarization:

No

Fiig: A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.