

View Online at <https://aerobasegroup.com/nsn/5935-01-128-2776>

Body Style:

Straight type

Overall Length:

4.900 inches

Overall Height:

0.755 inches

Overall Width:

0.400 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

4.650 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin left-hand at 9 o'clock and d shape socket right-hand at 9 o'clock

Insert Material Specification:

Mil-m-14, ty gdi-30 or ty sdg-f military specification single material response single mating end

Included Contact Quantity:

122 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.122 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.