

View Online at <https://aerobasegroup.com/nsn/5935-01-128-3588>

Thread Class:

2a

Thread Direction:

Right-hand

Overall Length:

Between 2.242 inches and 2.400 inches

Overall Height:

2.500 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

67 2nd mating end

Contact Removability:

Removable all mating ends all contact groupings

Polarization Method:

2 polarization posts

Shell Type:

Solid

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

24

Thread Size:

0.190 inches

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

Terminal Type:

Crimp all mating ends all contact groupings

Guide Design And Location:

Hexagon shape male post left-hand at 12 oclock and hexagon shape male post right-hand at 12 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

Insert Material Specification:

Mil-m-14 military specification single material response all mating ends

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.173 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.