

View Online at <https://aerobasegroup.com/nsn/5935-01-128-3605>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/screw locks

Overall Length:

0.850 inches

Overall Height:

0.965 inches

Overall Width:

0.250 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping and qq-c-533 federal specification single material response single mating end single contact grouping and qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or gst-40f military specification 2nd material response single mating end

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-55302/55 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.