

View Online at <https://aerobasegroup.com/nsn/5935-01-128-3627>

**Body Style:**

Angle, shape, internal coupling

**Overall Length:**

1.900 inches

**Overall Height:**

1.090 inches

**Overall Diameter:**

0.593 inches

**Environmental Protection:**

Shock proof and vibration proof

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Twin-x single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 120.0 and 240.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet slot

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end all contact groupings

**Terminal Location:**

Side single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 single mating end 2nd contact grouping

**Included Contact Type:**

Coaxial socket single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.