

View Online at <https://aerobasegroup.com/nsn/5935-01-128-3628>

Body Style:

Angle, shape, internal coupling

Overall Length:

1.900 inches

Overall Height:

1.090 inches

Overall Diameter:

0.593 inches

Environmental Protection:

Shock proof and vibration proof

Mating End Quantity:

1

Contact Position Arrangement Style:

Twin-x single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 100.0 and 130.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end all contact groupings

Terminal Location:

Side single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end 2nd contact grouping

Included Contact Type:

Coaxial socket single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.