Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-128-4533

# **Thread Class:**

2a and 2b

**Thread Direction:** 

Right-hand

# **Body Style:**

Straight shape w/screw locks

## **Overall Length:**

1.185 inches

#### **Overall Height:**

0.735 inches

**Overall Width:** 

0.305 inches

# **Environmental Protection:**

Corrosion resistant and shock resistant and thermal shock resistant and vibration resistant

#### Threaded Device Type:

Coupling facility

# Mating End Quantity:

1

# **Contact Position Arrangement Style:**

25 single mating end

# Contact Removability:

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

#### Shell Type:

Solid

#### **Connector Locking Method:**

Jackscrew-socket

# Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Glass single mating end and plastic diallyl phthalate single mating end

# NSN 5935-01-128-4533

Electrical Plug Connector - Page 2 of 2



## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, class 1 military specification single treatment response single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium and chromate

# Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 military specification all treatment responses

#### **Insert Material Specification:**

Mil-m-14, ty sdgf military specification single material response single mating end

#### **Included Contact Quantity:**

25 single mating end single contact grouping

#### Included Contact Type:

Round pin single mating end single contact grouping

#### **Special Features:**

18 in. Lg 26 awg wire leads

# **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.025 gold grains, troy

# Precious Material:

Gold

# **Thread Series Designator:**

Unc

# Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.