## NSN 5935-01-128-5789

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-128-5789 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/screw locks **Overall Length:** 0.935 inches **Overall Height:** 0.530 inches **Overall Width:** 0.305 inches **Environmental Protection:** Vibration resistant and moisture resistant and corrosion resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Jackscrew Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** 

Gold single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

#### **Terminal Type:**

Solder well single mating end single contact grouping

# **NSN 5935-01-128-5789**Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy 380.0
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.