

View Online at <https://aerobasegroup.com/nsn/5935-01-128-6081>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.250 inches

Overall Height:

0.580 inches

Overall Width:

0.390 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

34 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

48

Thread Size:

0.099 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdc-f military specification single material response single mating end

Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.034 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.