NSN 5935-01-128-6082

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-128-6082

Body Style:

Straight shape, internal coupling

Overall Length:

1.170 inches

Overall Diameter:

0.560 inches

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

0.195 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Crimp type

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

NSN 5935-01-128-6082 Electrical Plug Connector - Page 2 of 2



Shell Material:	
Copper alloy	
Shell Surface Treatment:	
Gold	
Shell Surface Treatment Specification:	
Mil-g-45204, type 2, cl 2 military specification single treatment response	
Shell Material Specification:	
Qq-b-626 federal specification single material response	
Insert Material Specification:	
L-p-403 federal specification single material response single mating end	
Included Contact Quantity:	
1 single mating end single contact grouping	
Included Contact Type:	
Coaxial pin single mating end single contact grouping	
Precious Material And Location:	
Contact and shell surfaces gold	
Precious Material And Weight:	
0.105 gold grains, troy	
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	