

View Online at <https://aerobasegroup.com/nsn/5935-01-128-9448>

Body Style:

Straight shape, internal coupling

Overall Length:

0.588 inches

Overall Diameter:

Between 0.532 inches and 0.538 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Detent

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-26074, cl 2 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Turret single mating end single contact grouping

Shell Surface Treatment:

Nickel and copper

Shell Surface Treatment Specification:

Mil-c-26074, cl 2 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Supplied with interfacial seal set back

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.