NSN 5935-01-129-0065

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-0065

Thread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removable single mating end single contact grouping Polarization Method:
Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Body Style: Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Overall Length: 1.234 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
1.234 inches Overall Diameter: 0.859 inches Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Overall Diameter: 0.859 inches Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
0.859 inches Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Environmental Protection: Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Back shell Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Mating End Quantity: 1 Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Contact Position Arrangement Style: Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Sep-98 single mating end Contact Removability: Removable single mating end single contact grouping
Contact Removability: Removable single mating end single contact grouping
Removable single mating end single contact grouping
Polarization Method:
Total Edition Motifica.
Keyway or multiple keyway
Insert Position In Deg:
342.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.219 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

NSN 5935-01-129-0065Electrical Plug Connector - Page 2 of 2



Shell Material:
Stainless steel
Shell Surface Treatment:
Gold and silver
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces gold and contact and shell surfaces silver
Precious Material And Weight:
0.015 gold grains, troy and 0.015 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0