Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-0084

Thread Class:
2b and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.423 inches
Overall Diameter:
0.406 inches
Distance From Mounting Shoulder To Front Face:
0.360 inches
Mounting Facility Thickness:
0.085 inches
Threaded Device Type:
Coupling facility and mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
36 and 80
Thread Size:
0.190 inches and 0.060 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorocarbon single mating end
Terminal Type:
Solder well single meting and single contact grouping

Solder well single mating end single contact grouping

NSN 5935-01-129-0084

Electrical Receptacle Connector - Page 2 of 2



Shell Material:

Steel

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Solder flange mounted with seven threaded holes equally spaced on a 0.300 diameter radius

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

. .

A039b0