NSN 5935-01-129-1636

Thread Class:

Right-hand **Body Style:**

Thread Direction:

Overall Length:
31.0 millimeters
Overall Diameter:
35.7 millimeters

Straight shape, internal coupling

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-1636

Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
17-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
330.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Thready Qty Per Inch (tpi):
10
Thread Size:
25.0 millimeters and 1.188 inches
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping

NSN 5935-01-129-1636Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Tolerance Class:
6g external
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Insert arrangement 17-35
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.055 silver grains, troy
Precious Material:
Silver
Test Data Document:
81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-dod-c-38999/26 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0