Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-1645

# Body Style:

Straight shape threaded

## **Overall Length:**

0.956 inches

## **Overall Diameter:**

Between 1.320 inches and 1.360 inches

## **Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and vibration proof and hermetic

## Distance From Mounting Shoulder To Front Face:

0.626 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

31 number 20 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

# Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

# Insert Position In Deg:

0.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Glass single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Steel

#### Shell Surface Treatment:

Tin



#### **Included Contact Quantity:**

31 single mating end single contact grouping

#### **Bushing Accommodation Hole Shape:**

Round

Included Contact Type:

Round pin single mating end single contact grouping

## **Special Features:**

Solder flange mounted

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.031 gold grains, troy

Precious Material:

Gold

#### **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-83723/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

#### **Demilitarization:**

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.