## NSN 5935-01-129-2743

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-2743
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
0.931 inches
Overall Height:
0.812 inches
Overall Width:
0.812 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.594 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.594 inches
Distance From Mounting Shoulder To Front Face:
0.447 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
12997 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
400.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
550.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-129-2743

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and nickel
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0