NSN 5935-01-129-2755

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-2755 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 1.440 inches **Overall Height:** Between 2.380 inches and 2.400 inches **Overall Width:** Between 2.865 inches and 2.885 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.143 inches and 0.155 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.845 inches and 1.855 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.495 inches and 2.505 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 212 single mating end **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Insert Material:**

Plastic diallyl phthalate glass filled single mating end

Shell Material:

Aluminum alloy

NSN 5935-01-129-2755

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 1 or 2 federal specification all treatment responses

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response or mil-p-19833, ty gdi-30f military specification single material response single mating end

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Specification Data:

81349-mil-c-28748/9 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.