Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-3427

## Body Style:

Right angle type

## **Overall Length:**

0.784 inches

## **Overall Width:**

0.358 inches

## **Body Height:**

0.289 inches

#### **Environmental Protection:**

Thermal shock resistant

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

# **Polarization Method:**

Mating end

# **Terminal Location:**

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic polyamide single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

#### **Included Contact Quantity:**

16 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.016 gold grains, troy

## **Precious Material:**

Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.