

View Online at <https://aerobasegroup.com/nsn/5935-01-129-4514>

Body Style:

Pcb, angle shape, external coupling

Overall Length:

0.600 inches

Overall Height:

0.540 inches

Overall Width:

0.375 inches

Environmental Protection:

Shock proof and vibration proof

Mating End Quantity:

1

Contact Position Arrangement Style:

Smb single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-39012/96 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.