## NSN 5935-01-129-6249



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-129-6249 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 2.375 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Environmental Protection:** Moisture proof and pressure proof and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Cable Entrance Diameter:** 1.412 inches **Distance From Mounting Shoulder To Front Face:** 0.718 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 28-42 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 18.0 and 149.0 and 192.0 and 259.0 Shell Type: Solid

**Connector Locking Method:** 

Externally threaded shell

## NSN 5935-01-129-6249

Electrical Receptacle Connector - Page 2 of 2



| Connector Cable Strain Relief Method:  |
|--|
| Cable clamp  |
| Thready Qty Per Inch (tpi):  |
| 16   |
| Thread Size:   |
| 1.812 inches   |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Rhodium single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material:   |
| Rubber single mating end   |
| Terminal Type:   |
| Crimp single mating end single contact grouping  |
| Shell Material:  |
| Stainless steel  |
| Included Contact Quantity:   |
| 42 single mating end single contact grouping   |
| Included Contact Type:   |
| Round pin single mating end single contact grouping  |
| Precious Material And Location:  |
| Contact surfaces rhodium and contact surfaces silver   |
| Precious Material And Weight:  |
| 0.042 rhodium grains, troy and 0.042 silver grains, troy   |
| Precious Material:   |
| Rhodium and silver   |
| Thread Series Designator:  |
| Un   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
|  |