NSN 5935-01-129-7511

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-7511 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, flange mount, external coupling **Overall Length:** 2.250 inches **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 30000.0 single mating end single contact grouping Shell Type: Potting **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): 18 Thread Size:

1.375 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-129-7511

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-750 federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Zz-r-765 assn standard single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0