

NSN 5935-01-129-7638 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-129-7638 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 2.055 inches **Overall Height:** 0.632 inches **Overall Width:** 0.330 inches **Environmental Protection:** Corrosion resistant and humidity resistant and thermal shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** 1.795 inches **Board Accommodated Length:** 1.375 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** Between 0.054 inches and 0.071 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

800.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

40

**Thread Size:** 

0.112 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# NSN 5935-01-129-7638

Electrical Receptacle Connector - Page 2 of 2



	11010	:	
Insert	IVIATE	er iai	G

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

## **Terminal Type:**

Pin single mating end single contact grouping

## **Insert Material Specification:**

Mil-p-19833, type gdi-30 military specification single material response single mating end or mil-m-14, type sdg military specification single material response single mating end

## **Included Contact Quantity:**

20 single mating end single contact grouping

#### **Included Contact Type:**

Leaf spring single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.