NSN 5935-01-129-9130



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-129-9130 **Body Style:** Straight shape, external coupling **Overall Length:** 0.838 inches **Overall Height:** 1.328 inches **Overall Width:** 1.328 inches **Unthreaded Mounting Hole Diameter:** 0.005 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.447 inches **Mating End Quantity: Contact Position Arrangement Style:** 18-32 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy

Shell Surface Treatment: Cadmium and nickel

NSN 5935-01-129-9130

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

32 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

She	lf I	l if	ο.
SHE		_,,	C.

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.