## NSN 5935-01-129-9136

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-129-9136 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.642 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 14s-2 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 120.0 Shell Type: Solid **Connector Locking Method:** Internally threaded shell **Thread Size:** 0.875 inches **Terminal Location:** 

Back single mating end single contact grouping

**Insert Material:** 

Silicon single mating end

## NSN 5935-01-129-9136

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-5015 spec.