Unc and unc



View Online at https://aerobasegroup.com/nsn/5935-01-130-0627

| ····· •·······························  |
|---|
| Thread Class:   |
| 2b and 2a   |
| Thread Direction:   |
| Right-hand and right-hand   |
| Body Style:   |
| Hood, top opening w/clamp   |
| Overall Length:   |
| 2.750 inches  |
| Overall Height:   |
| 3.250 inches  |
| Overall Width:  |
| 1.531 inches  |
| Cable Entrance Diameter:  |
| 1.188 inches  |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 25-104 single mating end  |
| Polarization Method:  |
| Jackscrew and shell   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Jackscrew-socket  |
| Connector Cable Strain Relief Method:   |
| Cable clamp   |
| Thread Size:  |
| 0.138 inches and 0.138 inches   |
| Insert Material:  |
| Plastic diallyl phthalate single mating end                                       |
| Shell Material:   |
| Steel   |
| Shell Surface Treatment:  |
| Passivate   |
| Insert Material Specification:  |
| Mil-m-14, sdg-f military specification single material response single mating end |
| Shell Guide Type And Location Designator:   |
| F slot  |
| Thread Series Designator:   |
|   |



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.