

View Online at <https://aerobasegroup.com/nsn/5935-01-130-1515>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, rectangular

Overall Length:

2.593 inches

Overall Height:

0.686 inches

Overall Width:

1.312 inches

Unthreaded Mounting Hole Diameter:

0.093 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.410 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.125 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

20 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

8.5 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Jackscrew

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape socket right-hand at 3 oclock

Insert Material Specification:

Mil-m-14f, ty sdgf military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.