Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-130-1601

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell Overall Length:
8.188 inches
Overall Diameter:
2.562 inches
Environmental Protection:
Thermal shock resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant
Cable Entrance Diameter:
Between 1.005 inches and 1.130 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
15.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Compression nut
Thready Qty Per Inch (tpi):
10
Thread Size:
2.250 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic single mating end

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end all contact groupings

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate and nickel

Shell Surface Treatment Specification:

Qq-p-416, ty ii federal specification 1st treatment response and qq-p-416, ty ii federal specification 2nd treatment response and qq-n-290

federal specification 3rd treatment response

Included Contact Quantity:

4 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Special Features:

Gland washer reworked

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.