

View Online at <https://aerobasegroup.com/nsn/5935-01-130-1660>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Overall Length:**

1.490 inches

**Overall Diameter:**

1.192 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and vibration proof

**Distance From Mounting Shoulder To Front Face:**

Between 0.761 inches and 0.781 inches

**Mounting Facility Thickness:**

Between 0.062 inches and 0.125 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

6-oct single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

85.0 and 155.0 and 220.0 and 325.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**End Application:**

2350-01-087-1095 tank, combat, full tracked

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.750 inches

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic epoxy single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074, cl 3 or 4, grade b military specification single treatment response

**Shell Material Specification:**

Qq-a-367 federal specification single material response

**Bushing Accommodation Hole Shape:**

Round w/flat

**Special Features:**

Jumper between contact number 3 and 6 and sealing plugs installed in grommet holes 1, 2, 4 and 5

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.030 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.