Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-130-3582

Body Style:

Angle shape, w/ or w/o cover

Overall Length:

4.990 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 4.367 inches and 4.373 inches

Overall Height:

2.900 inches

Overall Width:

3.740 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.195 inches and 0.202 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.997 inches and 3.003 inches

Mating End Quantity:

1

Contact Removability:

Removable single mating end 2nd contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Bracket

Terminal Location:

Back single mating end 2nd contact grouping

Contact Material:

Copper alloy single mating end 2nd contact grouping

Contact Surface Treatment:

Gold single mating end 2nd contact grouping and silver single mating end 2nd contact grouping

Terminal Type:

Crimp single mating end 2nd contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Included Contact Quantity:

1 single mating end 2nd contact grouping



Precious Material And Location: Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.142 gold grains, troy and 0.142 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-a-8625 spec.