

View Online at https://aerobasegroup.com/nsn/5935-01-130-3899

Body Material:
Plastic and glass
Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Top mount w/studs
Fabrication Method:
Molded
Overall Length:
1.740 inches
Overall Height:
1.973 inches
Overall Width:
0.530 inches
Mounting Hole Diameter:
0.116 inches
Body Mounting Hole Accommodation Length:
Between 1.105 inches and 1.115 inches
Body Mounting Hole Accommodation Width:
Between 0.550 inches and 0.560 inches
Distance Between Mounting Facility Centers:
Between 1.401 inches and 1.411 inches
Mounting Hole Style:
Rectangular, w/two mounting holes/slots
Contact Maximum Current Rating In Amps:
10.0
Contact Material:
Copper alloy
Contact Surface Treatment:
Gold and copper
Accommodated Contact Quantity:
8
Polarization Type:
Off center hole
Projection Length Below Mounting Surface:
Between 0.270 inches and 0.350 inches
Mounting Method:
Threaded stud
Mounting Type For Which Designed:

Chassis



Thready Qty Per Inch (tpi):

40 and 32

Thread Size:

0.112 inches and 0.190 inches

Contact Position Arrangement Style:

Dual in line

Special Features:

Item may be top or bottom mounted

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.008 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-s-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc and unf

Furnished Items And Quantity:

6 flat washer and 6 nut

Terminal Type And Quantity:

8 crimp

Specification Data:

81349-mil-s-12883/41 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A02300