NSN 5935-01-130-3908

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-130-3908

Body Style:

Straight shape threaded

Environmental Protection:

Corrosion resistant

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

5 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Zinc alloy

Shell Surface Treatment:

Nickel and copper

Included Contact Quantity:

5 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round keyed

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-01-130-3908

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0