## NSN 5935-01-130-6133



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-130-6133 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape w/cable clamp **Overall Diameter:** 1.770 inches **Body Angle In Deg:** 90.0 **Cable Entrance Diameter:** Between 0.625 inches and 0.937 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-27 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **Distance From Centerline To Connector End:** 3.000 inches **Distance From Centerline To Cable End:** 3.688 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end all contact groupings

**Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-01-130-6133

Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate and nickel
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-5015 spec.